

IP56 Weatherproof electrical box.
Discuss optional electrical items with Marsden Engineering.

Stainless steel swing-axles in polymer bearings (lubrication free)

Motion sensor prox switch is hoseproof and permanently wired for reliability; placed high up out of harm's way

Typical mounting: U-Bolts to Post or Building Column (76mm to 125mm SHS). Or, clip to H-column flange with Lindaptors, or bolt to wall, etc)

Optional Feature - Plug & Outlet:

Motor cable may be unplugged and the 3-pin outlet used for 10 Amp hand tools. The motor or entire brushing unit may be removed for service without requiring an electrician.

Motor, single phase: IP55 weather resistant, or optional IP56 hose resistant

Guard recessed into brush for maximum tangle protection

The Brush swings side-to-side and back-and-forth for maximum coverage

Selector Isolator switch

Brush easily removed; turn end-for-end to even out wear. Reconditioned by replacing worn-out bristles.

WHY USE A COW BRUSH?

Electric fences and treeless paddocks leave little for a cow to scratch on; but a self-grooming brush does much more than save your gates and her hide from damage. It removes dirt and parasites, and massages to promote healthy blood flow and wakefulness, and hence increased appetite and improved metabolism. A happy, healthy cow is a more productive asset.

END VIEW

SIDE VIEW

Caution: Due to ongoing development, some features on this promotional illustration may not exactly match the product being sold. !

Marsdezyn - Presents the...

Moo-sseuse

Cow massage Brush



1 McKechnie st (off Majors road) Geraldine 7930		PO Box 96 Phone: 03 693 9634 After hours: 027 242 2110	
www.marsdenengineering.co.nz		email: marsdeneng@gmail.com	
INITIALS & REV DATE IM -2015	A3 3rd L Projection	DRAWING NUMBER CB-BRUSH-000	SHEET REVISION 1 of 1 2